

# Trapping of $^{85}\text{Rb}$ atoms by optical pumping between metastable hyperfine states

N Cooper and T Freegarde

School of Physics and Astronomy, University of Southampton, Highfield,  
Southampton SO17 1BJ, UK

E-mail: [nlc2g09@soton.ac.uk](mailto:nlc2g09@soton.ac.uk)

**Abstract.** We describe an atom trapping mechanism based upon differential optical pumping between metastable hyperfine states by partially-displaced laser beams in the absence of a magnetic field. With realistic laser powers, trap spring constants should match or exceed those typical of magneto-optical traps, and highly flexible tailored trap shapes should be achievable. In a proof-of-principle experiment, we have combined a 1D implementation with magneto-optical trapping in the orthogonal directions, capturing  $\sim 10^4$   $^{85}\text{Rb}$  atoms.

PACS numbers: 37.10.Gh, 32.10.Fn


## 1. Introduction

Optical atom traps based on the force accompanying the absorption and spontaneous re-emission of radiation are vital tools in atomic physics. The most widely used is the magneto-optical trap (MOT) [1], and many experiments can be performed directly on the atom cloud that it forms [2, 3]; when optical dipole or magnetic traps are required, the MOT is usually used for the initial loading into a generally conservative trapping potential [4, 5]. A few alternatives to the MOT have been proposed [6, 7, 8], each with its advantages and disadvantages. Here, we propose a further alternative, whereby the trap depends upon differential pumping between metastable hyperfine states according to the spatially-varying balance of intensities between different wavelengths of illumination. This metastable optical pumping (MOP) trap may be directly combined with Doppler cooling, but lacks some of the enhanced cooling mechanisms associated with the MOT and is experimentally more complex when implemented in more than one dimension. However, because it depends upon a spatially-varying optical rather than magnetic field, it is more readily sculpted and capable of stronger spring constants. It can in principle operate between the hyperfine states of any atom with a non-zero nuclear spin, or between other states that are sufficiently long-lived.

The principle underlying our trapping scheme is that if two laser beams address transitions involving two different, long-lived energy levels, then scattering from one beam can be elevated over scattering from the other by optically pumping the atomic population into the appropriate state. This allows the optical Earnshaw theorem [9] to be circumvented and an optical atom trap to be created.

Figures 1 and 2 illustrate the key elements in our scheme, which relies upon the spatially-dependent balance between two opposing optical forces, reflecting in turn the spatial dependence of the populations of the metastable levels A and B. Permitted electric dipole transitions exist between states C and A, D and A, D and B, and E and B. Atoms in the metastable state A experience an average scattering force to the right from the power imbalance between the left and right traveling beams tuned to the A-C transition, while atoms in the alternative metastable state B experience an average scattering force in the opposite direction from the imbalance between the beams tuned to the B-E transition. Pump beams A-D and B-D, which propagate across the scattering beams and are individually balanced to exert no average force, provide spatially-dependent transfer of population between the metastable levels. By shaping the pump beams using a mask or spatial light modulator (SLM), the magnitude and direction of the net force upon the atoms may be tailored to the desired trap shape with a near-wavelength resolution that is several orders of magnitude finer than may usually be achieved by shaping the magnetic fields of a magneto-optical trap.

The trap described thus far operates in just one dimension, as the balance of forces within different pushing beam pairs can only be independently modified if the pushing




**Figure 1.** Pumping scheme for a MOP trap. The leftmost part shows a generalized level scheme and allowed transitions between the metastable levels A, B and upper radiative levels C, D and E. The corresponding levels of  $^{85}\text{Rb}$  used in our experiments are shown to the right, the  $5\text{P}_{3/2}$  F=2 and F=3 states together corresponding to the generalized level D.

beam pairs address distinct pairs of metastable levels. Three dimensional trapping would therefore be possible if a third metastable level were included in the pumping scheme. However, the most straightforward extension to two and three dimensions will be by time-multiplexing, as illustrated schematically in figure 3, whereby independent one-dimensional traps operate along orthogonal axes, with high frequency switching of the laser beams to alternate between the separate traps. The intensity profile of the pumping beams in two or three dimensional traps could be set using a single 2D SLM if this switching were synchronized with the SLM frame-update frequency, which would also facilitate dynamic adjustment of the trap shape. A similar time-multiplexing scheme, in which alternation between two 2D magneto-optical traps results in a full, 3D MOT, has recently been demonstrated experimentally [10].


## 2. Experimental implementation

In our experimental implementation using atomic  $^{85}\text{Rb}$ , we use the  $5\text{S}_{1/2}$  F=2 and F=3 ‘ground’ hyperfine states as the metastable levels A and B respectively and the  $5\text{P}_{3/2}$  F=1 to F=4 states as the upper radiative levels C, D and E, as shown in figure 1: the F=2 and F=3 states together correspond to level D and allow favourable branching ratios to be chosen for the respective pumping beams. All our beams are detuned slightly to the red of the relevant atomic transitions to allow them to perform the additional function of Doppler cooling.


For practical convenience, we combine the functions of the A-C rightward pushing beam and the A-D pumping beam by using a single rightward-directed beam tuned to the A-D ( $5\text{S}_{1/2}$  F=2  $\leftrightarrow$   $5\text{P}_{3/2}$  F=3) transition. In the absence of the other pumping beam



**Figure 2.** Beam geometry for a 1D MOP trap. The transition addressed by each beam is that shown in figure 1 by the same arrow colour and border. Larger arrows for the horizontal ‘pushing’ beams indicate higher intensities. The intensity distributions of the vertical ‘pumping’ beams determine the force profile of the trap, although each is balanced against its counter propagating twin to eliminate radiation forces from the pumping beams themselves.



**Figure 3.** Proposed beam geometry for 2D trapping via time-multiplexing. The pairs of opposing ‘pushing’ beams would only be active along either the x or y axis at any given time, with switching between these beams being achieved, for example, via the use of a Pockels cell and polarising beam splitter. The spatial light modulator (SLM) would be used to switch the intensity profile of the ‘pumping’ beam, with simultaneous sculpting of the A-D and B-D beams being possible through, for example, the use of distinct spatial regions of the SLM.



**Figure 4.** Images of the atom clouds formed by a 1D MOP trap combined with 2D magneto-optical trapping in the orthogonal directions. In (b) a small obstruction was introduced into the B-D beam, casting a geometric shadow into the trapping region and thus generating two adjacent trapping sites separated by a small area of reduced atom density.

(B-D), this concentrates atomic population in the  $5\text{S}_{1/2}$   $F=3$  ground hyperfine state B, where atoms experience only the leftward force exerted by the pushing beam pair B-E, which is tuned to the  $5\text{S}_{1/2}$   $F=3 \leftrightarrow 5\text{P}_{3/2}$   $F=4$  transition and which experimentally corresponds to a bright beam incident from the right and its attenuated reflection. Where the atoms are also illuminated by the pumping beam B-D, tuned to the  $5\text{S}_{1/2}$   $F=3 \leftrightarrow 5\text{P}_{3/2}$   $F=2$  transition, atoms may be pumped into the ground hyperfine state A, where they experience a rightward force due to the A-D beam that can overcome that due to scattering of the B-E pushing beam. The net force upon the atoms depends upon the balance between the metastable state populations and hence upon the local intensity of the B-D pumping beam: where this is high there is a net force to the right, where it is weak the net force is to the left, and the trap centre forms where the net force is zero on the right-hand edge of the B-D pumping beam.

As a proof-of-principle experiment, we combined a two-dimensional magneto-optical trap, usually used to bring an atom cloud close to a microstructured surface, with a one-dimensional MOP trap in the orthogonal direction. All beams along the trapping axis of the MOP trap were linearly polarised to eliminate magneto-optical forces in this direction. Around  $10^4$   $^{85}\text{Rb}$  atoms were captured - about a third of the number obtained with a full 3-D MOT in this configuration [14]. The trapped atom cloud is shown in figure 4(a). To demonstrate the potential for sculpting of the trap geometry, a small obstruction was introduced into the B-D beam, casting a geometric shadow into the trapping region and thereby creating two adjacent trapping regions as shown in figure 4(b).

### 3. Theoretical Analysis

To gain an approximate quantitative understanding of the mechanism, we model the atoms as five-level systems governed by a set of rate equations, with stimulated and spontaneous transition rates between, for example, states E and B given by  $\tau_{\text{EB}}I_{\text{EB}}$  and  $\Gamma_{\text{EB}}$  respectively, where  $I_{\text{EB}}$  is the intensity of the laser light tuned to the relevant transition. Transition rates between other pairs of states are labeled similarly. We ignore the coupling of the beams to non-target transitions and neglect the atomic coherences which, if the lasers are detuned by the order of a linewidth for Doppler cooling, are unlikely to play a significant role — theoretical models that ignore atomic coherences have been shown to accurately predict experimental results under similar circumstances [15]. As the timescales associated with motion within the trap are much longer than those associated with optical pumping, we use the steady-state populations and time-averaged forces to determine the trap properties. We derive the stimulated transition rates by considering the steady-state solution of the optical Bloch equations for a two-level system characterised by a spontaneous decay rate  $\Gamma$ , when illuminated by a beam of detuning  $\delta$  and intensity  $I$ , with Rabi frequency  $\Omega$ , and comparing this to the steady-state populations in a simple rate equation model. Equating the results for the upper state population, we obtain

$$\frac{\Omega^2/4}{\delta^2 + \Omega^2/2 + \Gamma^2/4} = \frac{\tau I}{2\tau I + \Gamma}, \quad (1)$$

and therefore, defining the dipole matrix element  $\langle \text{E}|x|\text{B} \rangle$  between two levels as  $X_{\text{EB}}$ , we obtain

$$\tau_{\text{EB}} = \frac{\Omega_{\text{EB}}^2 \Gamma_{\text{EB}}}{4I_{\text{EB}}(\delta_{\text{EB}}^2 + \Gamma_{\text{EB}}^2/2)} = \frac{e^2 |X_{\text{EB}}|^2 \Gamma_{\text{EB}}}{2\hbar^2 c \epsilon_0 (\delta_{\text{EB}}^2 + \Gamma_{\text{EB}}^2/2)} \quad (2)$$

and similar expressions for the other transitions. The rate equations governing the system are then:

$$\frac{d\text{E}}{dt} = (\text{B} - \text{E})\tau_{\text{EB}}I_{\text{EB}} - \text{E}\Gamma_{\text{EB}}, \quad (3)$$

$$\frac{d\text{D}_3}{dt} = (\text{A} - \text{D}_3)\tau_{\text{D}_3\text{A}}I_{\text{D}_3\text{A}} - \text{D}_3\Gamma_{\text{D}_3\text{B}} - \text{D}_3\Gamma_{\text{D}_3\text{A}}, \quad (4)$$

$$\frac{d\text{D}_2}{dt} = (\text{B} - \text{D}_2)\tau_{\text{D}_2\text{B}}I_{\text{D}_2\text{B}} - \text{D}_2\Gamma_{\text{D}_2\text{B}} - \text{D}_2\Gamma_{\text{D}_2\text{A}}, \quad (5)$$

$$\frac{d\text{B}}{dt} = (\text{E} - \text{B})\tau_{\text{EB}}I_{\text{EB}} + (\text{D}_2 - \text{B})\tau_{\text{D}_2\text{B}}I_{\text{D}_2\text{B}} + \text{E}\Gamma_{\text{EB}} + \text{D}_3\Gamma_{\text{D}_3\text{B}} + \text{D}_2\Gamma_{\text{D}_2\text{B}}, \quad (6)$$

and

$$\frac{d\text{A}}{dt} = (\text{D}_3 - \text{A})\tau_{\text{D}_3\text{A}}I_{\text{D}_3\text{A}} + \text{D}_3\Gamma_{\text{D}_3\text{A}} + \text{D}_2\Gamma_{\text{D}_2\text{A}}, \quad (7)$$

where A-E represent the populations of the states A-E shown in figure 1. Setting all the time derivatives to zero and solving these equations yields the steady-state populations of the five levels, as described in the Appendix, from which the time-averaged force on an atom may be found to be

$$\bar{\mathbf{F}} = (B_s - E_s)\tau_{EB}I_{EB}\mathbf{p}_{EB} + (A_s - D_{3s})\tau_{D_{3A}}I_{D_{3A}}\mathbf{p}_{D_{3A}} + (B_s - D_{2s})\tau_{D_{2B}}I_{D_{2B}}\mathbf{p}_{D_{2B}}, \quad (8)$$

where  $\mathbf{p}_{EB}$  are the (vector) mean photon momenta associated with scattering of the corresponding laser beams and the subscript  $s$  indicates the steady-state populations. Substitution of some realistic experimental parameters allows comparison of the restoring force and its gradient in the MOP trap with values typical of a MOT. For the one-dimensional trap of figure 1, with 10 mW each in 3 mm diameter beams and 30% attenuation of the B-E beam on reflection, detunings of  $\sim 2\Gamma$ , and with the pushing beams propagating along the  $z$ -axis, we hence have beam parameters

$$I_{EB}(x, y, z) = 1.7I_0 \exp \left[ -2(x^2 + y^2)/r_0^2 \right], \quad (9)$$

$$I_{D_{3A}}(x, y, z) = I_0 \exp \left[ -2(x^2 + y^2)/r_0^2 \right], \quad (10)$$


$$I_{D_{2B}}(x, y, z) = 2I_0 \exp \left[ -2(x^2 + z^2)/r_0^2 \right], \quad (11)$$

$$\mathbf{p}_{EB} = \frac{-0.18\hbar}{\lambda} \hat{\mathbf{z}}, \quad \mathbf{p}_{D_{3A}} = \frac{\hbar}{\lambda} \hat{\mathbf{z}} \quad \& \quad \mathbf{p}_{D_{2B}} = \mathbf{0}, \quad (12)$$

where  $I_0 = 2.8 \times 10^3 \text{ W m}^{-2}$  and  $r_0 = 1.5 \text{ mm}$ . Using the  $^{85}\text{Rb}$  parameters from [11] and assuming the trapping light to be isotropically polarised, we hence obtain the trapping force profile shown in figure 5, which shows the trap centre to be about 1.6 mm from the axis of the B-D laser beam and the trap to have a spring constant around  $4 \times 10^{-18} \text{ N m}^{-1}$  — about an order of magnitude greater than in a typical MOT with a magnetic field gradient of  $\sim 0.1 \text{ T m}^{-1}$ .

#### 4. Applications and Conclusions

One potential application of the MOP trap is to experiments where a particular atom density distribution is required, for example for the efficient loading of an array of conservative atom traps of the type discussed in [12, 13]. It might also be helpful to combine the large spring constant and highly flexible shape of the MOP trap with the efficient cooling and loading of a MOT in order to obtain a very high density of trapped atoms. A significant advantage of the MOP trap, however, is that it requires no magnetic field or field gradient, and is therefore compatible with trapping near to magnetic materials and structures that would disturb a conventional magneto-optical trap. The absence of a magnetic component also allows the trapping potential to be modified more rapidly than in a MOT, where inductive effects usually place a practical limit on the rate at which the magnetic field can be adjusted. Furthermore, as the trapping mechanism does not rely upon population transfer between Zeeman sublevels,



**Figure 5.** Time-averaged  $z$  component of the radiation pressure force on an atom as a function of its position on the  $z$  axis for a one dimensional MOP trap based on the scheme shown in figures 1 and 2 and the parameters given in (9–12). The origin is taken to be on the axis of the B-D beam.

MOP traps share with those of [8] the option to spin-polarise the atom cloud to some degree if required.

Zeeman assisted slowing and Sisyphus cooling are not inherently present in a MOP trap as they are in a MOT; this means that a MOP trap is likely to produce a smaller atom cloud with a higher temperature than that generated by a typical MOT. The experimental complexity is also greater for multi-dimensional traps. However, as the optical polarization plays no role in the MOP trapping mechanism, there is no reason why, in the presence of an additional magnetic field, the beam polarizations could not be chosen so as to promote sub-Doppler cooling for lower temperatures and higher loading rates.

## 5. Acknowledgements

This work was supported by the UK EPSRC grants EP/E039839/1 and EP/E058949/1.

## Appendix

Given here are the full steady-state solutions to the rate equations for the five-level system. In order to simplify the formulae we introduce the following notation:

$$K_1 = \frac{\tau_{\text{EB}} I_{\text{EB}}}{\tau_{\text{EB}} I_{\text{EB}} + \Gamma_{\text{EB}}}, \quad (\text{A.1})$$

$$K_2 = \frac{\tau_{\text{D}_3\text{A}} I_{\text{D}_3\text{A}}}{\tau_{\text{D}_3\text{A}} I_{\text{D}_3\text{A}} + \Gamma_{\text{D}_3\text{B}} + \Gamma_{\text{D}_3\text{A}}}, \quad (\text{A.2})$$

$$K_3 = \frac{\tau_{\text{D}_2\text{B}} I_{\text{D}_2\text{B}}}{\tau_{\text{D}_2\text{B}} I_{\text{D}_2\text{B}} + \Gamma_{\text{D}_2\text{B}} + \Gamma_{\text{D}_2\text{A}}}, \quad (\text{A.3})$$

and

$$K_4 = \frac{-K_3 \Gamma_{\text{D}_2\text{A}}}{\Gamma_{\text{D}_3\text{A}} K_2 + (K_2 - 1) \tau_{\text{D}_3\text{A}} I_{\text{D}_3\text{A}}}. \quad (\text{A.4})$$

For the steady state populations of the five levels we then obtain:

$$\text{B}_s = (1 + K_1 + K_2 K_4 + K_3 + K_4)^{-1}, \quad (\text{A.5})$$

$$\text{E}_s = K_1 \text{B}_s, \quad (\text{A.6})$$

$$\text{D}_{3s} = K_2 K_4 \text{B}_s, \quad (\text{A.7})$$

$$\text{D}_{2s} = K_3 \text{B}_s, \quad (\text{A.8})$$

and

$$\text{A}_s = K_4 \text{B}_s. \quad (\text{A.9})$$

Combining these with (8)–(12) allows the derivation of a full expression for the (time-averaged) force as a function of position,  $\bar{\mathbf{F}}(x, y, z)$ . Once this is established, the trap centre can be found by setting  $\bar{\mathbf{F}}(x, y, z) = \mathbf{0}$  and solving for the coordinates at which this equality holds. It is then possible to calculate the spring constant along a given axis by computing  $\left. \frac{d\bar{F}_i}{dx_i} \right|_{\text{trap centre}}$ .

## References

- [1] Raab E, Prentiss M, Cable A, Chu S and Pritchard D 1987 *Phys. Rev. Lett.* **59** 2631
- [2] Gabbanini C, Fioretti A, Lucchesini A, Gozzini S and Mazzoni M 2000 *Phys. Rev. Lett.* **84** 2814
- [3] Li W, Mourachko I, Noel M and Gallagher T 2003 *Phys. Rev. A* **67** 052502
- [4] Roy A, Jing A and Barrett M 2012 *New J. Phys.* **14** 093007
- [5] Viteau M, Radogostowicz J, Chotia A, Bason M, Malossi N, Fuso F, Ciampini D, Morsch O, Ryabtsev I and Arimondo E 2010 *J. Phys. B* **43** 155301
- [6] Pritchard D, Raab E, Bagnato V, Wieman C and Watts R 1986 *Phys. Rev. Lett.* **57** 310-313
- [7] Bouyer P, Lemonde P, Dahan M, Michaud A, Salomon C and Dalibard J 1994 *Europhys. Lett.* **27** 569
- [8] Walker T, Feng P, Hoffmann D and Williamson R 1992 *Phys. Rev. Lett.* **69** 2168
- [9] Ashkin A and Gordon J 1983 *Opt. Lett.* **8** 511-513
- [10] Rushton J, Bateman J, Aldous M and Himsworth M (in preparation) ‘A Dynamic Magneto-Optical Trap for Atom Chips’
- [11] Steck D 2012 <http://steck.us/alkalidata> (revision 2.1.5)
- [12] Kruse J, Gierl C, Schlosser M, and Birk G 2010 *Phys. Rev. A* **81** 060308(R)
- [13] Fortágh J and Zimmermann C 2007 *Rev. Mod. Phys.* **79** 235-289
- [14] Ohadi H, Himsworth M, Xuereb A and Freegarde T 2009 *Opt. Expr.* **17** 23003
- [15] Himsworth M and Freegarde T 2010 *Phys. Rev. A* **81** 023423